

# **Fontconfig Developers Reference, Version 2.3.97**

**Keith Packard**  
**HP Cambridge Research Lab**

## **1. DESCRIPTION**

Fontconfig is a library designed to provide system-wide font configuration, customization and application access.

## **2. FUNCTIONAL OVERVIEW**

Fontconfig contains two essential modules, the configuration module which builds an internal configuration from XML files and the matching module which accepts font patterns and returns the nearest matching font.

### **2.1. FONT CONFIGURATION**

The configuration module consists of the FcConfig datatype, libexpat and FcConfigParse which walks over an XML tree and ammends a configuration with data found within. From an external perspective, configuration of the library consists of generating a valid XML tree and feeding that to FcConfigParse. The only other mechanism provided to applications for changing the running configuration is to add fonts and directories to the list of application-provided font files.

The intent is to make font configurations relatively static, and shared by as many applications as possible. It is hoped that this will lead to more stable font selection when passing names from one application to another. XML was chosen as a configuration file format because it provides a format which is easy for external agents to edit while retaining the correct structure and syntax.

Font configuration is separate from font matching; applications needing to do their own matching can access the available fonts from the library and perform private matching. The intent is to permit applications to pick and choose appropriate functionality from the library instead of forcing them to choose between this library and a private configuration mechanism. The hope is that this will ensure that configuration of fonts for all applications can be centralized in one place. Centralizing font configuration will simplify and regularize font installation and customization.

## 2.2. FONT PROPERTIES

While font patterns may contain essentially any properties, there are some well known properties with associated types. Fontconfig uses some of these properties for font matching and font completion. Others are provided as a convenience for the applications rendering mechanism.

Property Definitions

Property	CPP Symbol	Type	Description
<hr/>			
family	FC_FAMILY	String	Font family names
familylang	FC_FAMILYLANG	String	Language cooresponding to each family name
style	FC_STYLE	String	Font style. Overrides weight and slant
stylelang	FC_STYLERLANG	String	Language cooresponding to each style name
fullname	FC_FULLSCREEN	String	Font face full name where different from family and family + style
fullnamelang	FC_FULLSCREENLANG	String	Language cooresponding to each fullname
slant	FC_SLANT	Int	Italic, oblique or roman
weight	FC_WEIGHT	Int	Light, medium, demibold, bold or black
size	FC_SIZE	Double	Point size
width	FC_WIDTH	Int	Condensed, normal or expanded
aspect	FC_ASPECT	Double	Stretches glyphs horizontally before hinting
pixelsize	FC_PIXEL_SIZE	Double	Pixel size
spacing	FC_SPACING	Int	Proportional, dual-width, monospace or charcell
foundry	FC_FOUNDRY	String	Font foundry name
antialias	FC_ANTIALIAS	Bool	Whether glyphs can be antialiased
hinting	FC_HINTING	Bool	Whether the rasterizer should use hinting
hintstyle	FC_HINT_STYLE	Int	Automatic hinting style
verticallayout	FC_VERTICAL_LAYOUT	Bool	Use vertical layout
autohint	FC_AUTOHINT	Bool	Use autohinter instead of normal hinter
globaladvance	FC_GLOBAL_ADVANCE	Bool	Use font global advance data
file	FC_FILE	String	The filename holding the font
index	FC_INDEX	Int	The index of the font within the file
ftface	FC_FT_FACE	FT_Face	Use the specified FreeType face object
rasterizer	FC_RASTERIZER	String	Which rasterizer is in use
outline	FC_OUTLINE	Bool	Whether the glyphs are outlines
scalable	FC_SCALABLE	Bool	Whether glyphs can be scaled
scale	FC_SCALE	Double	Scale factor for point->pixel conversions

dpi	FC_DPI	Double	Target dots per inch
rgba	FC_RGBA	Int	unknown, rgb, bgr, vrgb, vbgr, none - subpixel geometry
minspace	FC_MINSPACE	Bool	Eliminate leading from line spacing
charset	FC_CHARSET	CharSet	Unicode chars encoded by the font
lang	FC_LANG	String	List of RFC-3066-style languages this font supports
fontversion	FC_FONTVERSION	Int	Version number of the font
capability	FC_CAPABILITY	String	List of layout capabilities in the font
embolden	FC_EMBOULDEN	Bool	Rasterizer should synthetically embolden the font

## 3. Datatypes

Fontconfig uses abstract datatypes to hide internal implementation details for most data structures. A few structures are exposed where appropriate.

### 3.1. FcChar8, FcChar16, FcChar32, FcBool

These are primitive datatypes; the FcChar\* types hold precisely the number of bits stated (if supported by the C implementation). FcBool holds one of two CPP symbols: FcFalse or FcTrue.

### 3.2. FcMatrix

An FcMatrix holds an affine transformation, usually used to reshape glyphs. A small set of matrix operations are provided to manipulate these.

```
typedef struct _FcMatrix {
    double xx, xy, yx, yy;
} FcMatrix;
```

### 3.3. Fc CharSet

An Fc CharSet is an abstract type that holds the set of encoded unicode chars in a font. Operations to build and compare these sets are provided.

### 3.4. Fc Type

Tags the kind of data stored in an Fc Value.

### 3.5. Fc Value

An Fc Value object holds a single value with one of a number of different types. The 'type' tag indicates which member is valid.

```
typedef struct _FcValue {
    FcType type;
    union {
        const FcChar8 *s;
        int i;
        FcBool b;
        double d;
        const FcMatrix *m;
        const Fc CharSet *c;
    } u;
} FcValue;
```

#### FcValue Members

Type	Union member	Datatype
<hr/>		
FcTypeVoid	(none)	(none)
FcTypeInteger	i	int
FcTypeDouble	d	double
FcTypeString	s	char *
FcTypeBool	b	b
FcTypeMatrix	m	FcMatrix *
FcTypeCharSet	c	Fc CharSet *

## 3.6. FcPattern

holds a set of names with associated value lists; each name refers to a property of a font. FcPatterns are used as inputs to the matching code as well as holding information about specific fonts. Each property can hold one or more values; conventionally all of the same type, although the interface doesn't demand that.

## 3.7. FcFontSet

```
typedef struct _FcFontSet {
    int nfont;
    int sfont;
    FcPattern **fonts;
} FcFontSet;
```

An FcFontSet contains a list of FcPatterns. Internally fontconfig uses this data structure to hold sets of fonts. Externally, fontconfig returns the results of listing fonts in this format. 'nfont' holds the number of patterns in the 'fonts' array; 'sfont' is used to indicate the size of that array.

## 3.8. FcStrSet, FcStrList

FcStrSet holds a list of strings that can be appended to and enumerated. Its unique characteristic is that the enumeration works even while strings are appended during enumeration. FcStrList is used during enumeration to safely and correctly walk the list of strings even while that list is edited in the middle of enumeration.

## 3.9. FcObjectSet

```
typedef struct _FcObjectSet {
    int nobject;
    int sobject;
    const char **objects;
} FcObjectSet;
```

holds a set of names and is used to specify which fields from fonts are placed in the the list of returned patterns when listing fonts.

## 3.10. FcObjectType

```
typedef struct _FcObjectType {
    const char *object;
    FcType type;
} FcObjectType;
```

marks the type of a pattern element generated when parsing font names. Applications can add new object types so that font names may contain the new elements.

## 3.11. FcConstant

```
typedef struct _FcConstant {
    const FcChar8 *name;
    const char *object;
    int value;
} FcConstant;
```

Provides for symbolic constants for new pattern elements. When 'name' is seen in a font name, an 'object' element is created with value 'value'.

## 3.12. FcBlanks

holds a list of Unicode chars which are expected to be blank; unexpectedly blank chars are assumed to be invalid and are elided from the charset associated with the font.

## 3.13. FcFileCache

holds the per-user cache information for use while loading the font database. This is built automatically for the current configuration when that is loaded. Applications must always pass '0' when one is requested.

## 3.14. FcConfig

holds a complete configuration of the library; there is one default configuration, other can be constructed from XML data structures. All public entry points that need global data can take an optional FcConfig\* argument; passing 0 uses the default configuration. FcConfig objects hold two sets of fonts, the first

contains those specified by the configuration, the second set holds those added by the application at run-time. Interfaces that need to reference a particular set use one of the FcSetName enumerated values.

## 3.15. FcSetName

Specifies one of the two sets of fonts available in a configuration; FcSetSystem for those fonts specified in the configuration and FcSetApplication which holds fonts provided by the application.

## 3.16. FcResult

Used as a return type for functions manipulating FcPattern objects.

FcResult Values	
Result Code	Meaning
-----	-----
FcResultMatch	Object exists with the specified ID
FcResultNoMatch	Object doesn't exist at all
FcResultTypeMismatch	Object exists, but the type doesn't match
FcResultNoId	Object exists, but has fewer values than specified
FcResultOutOfMemory	Malloc failed

## 3.17. FcAtomic

Used for locking access to config files. Provides a safe way to update configuration files.

# 4. FUNCTIONS

These are grouped by functionality, often using the main datatype being manipulated.

## 4.1. Initialization

These functions provide some control over how the library is initialized.

## **FcInitLoadConfig**

### **Name**

`FcInitLoadConfig` — load configuration

### **Synopsis**

```
#include <fontconfig.h>
FcConfig * FcInitLoadConfig(void);
```

### **Description**

Loads the default configuration file and returns the resulting configuration. Does not load any font information.

### **Version**

Fontconfig version 2.3.97

## **FcInitLoadConfigAndFonts**

### **Name**

`FcInitLoadConfigAndFonts` — load configuration and font data

### **Synopsis**

```
#include <fontconfig.h>
FcConfig * FcInitLoadConfigAndFonts(void);
```

## Description

Loads the default configuration file and builds information about the available fonts. Returns the resulting configuration.

## Version

Fontconfig version 2.3.97

# FcInit

## Name

`FcInit` — initialize fontconfig library

## Synopsis

```
#include <fontconfig.h>
FcBool FcInit(void);
```

## Description

Loads the default configuration file and the fonts referenced therein and sets the default configuration to that result. Returns whether this process succeeded or not. If the default configuration has already been loaded, this routine does nothing and returns `FcTrue`.

## Version

Fontconfig version 2.3.97

## FcFini

### Name

FcFini — finalize fonconfig library

### Synopsis

```
#include <fontconfig.h>
void FcFini(void);
```

### Description

Frees all data structures allocated by previous calls to fontconfig functions. Fontconfig returns to an uninitialized state, requiring a new call to one of the FcInit functions before any other fontconfig function may be called.

### Version

Fontconfig version 2.3.97

## FcGetVersion

### Name

FcGetVersion — library version number

### Synopsis

```
#include <fontconfig.h>
int FcGetVersion(void);
```

## **Description**

Returns the version number of the library.

## **Version**

Fontconfig version 2.3.97

# **FcInitReinitialize**

## **Name**

`FcInitReinitialize` — re-initialize library

## **Synopsis**

```
#include <fontconfig.h>
FcBool FcInitReinitialize(void);
```

## **Description**

Forces the default configuration file to be reloaded and resets the default configuration.

## **Version**

Fontconfig version 2.3.97

## **FcInitBringUptoDate**

### **Name**

`FcInitBringUptoDate` — reload configuration files if needed

### **Synopsis**

```
#include <fontconfig.h>
FcBool FcInitBringUptoDate(void);
```

### **Description**

Checks the rescan interval in the default configuration, checking the configuration if the interval has passed and reloading the configuration if when any changes are detected.

### **Version**

Fontconfig version 2.3.97

## **4.2. FcPattern**

An `FcPattern` is an opaque type that holds both patterns to match against the available fonts, as well as the information about each font.

## **FcPatternCreate**

### **Name**

`FcPatternCreate` — Create a pattern

## Synopsis

```
#include <fontconfig.h>
FcPattern * FcPatternCreate(void);
```

## Description

Creates a pattern with no properties; used to build patterns from scratch.

## Version

Fontconfig version 2.3.97

# **FcPatternDestroy**

## Name

`FcPatternDestroy` — Destroy a pattern

## Synopsis

```
#include <fontconfig.h>
void FcPatternDestroy(FcPattern *p);
```

## Description

Destroys a pattern, in the process destroying all related values.

## Version

Fontconfig version 2.3.97

## FcPatternEqual

### Name

FcPatternEqual — Compare patterns

### Synopsis

```
#include <fontconfig.h>
FcBool FcPatternEqual(const FcPattern *pa, const FcPattern *pb);
```

### Description

Returns whether *pa* and *pb* are exactly alike.

### Version

Fontconfig version 2.3.97

## FcPatternEqualSubset

### Name

FcPatternEqualSubset — Compare portions of patterns

### Synopsis

```
#include <fontconfig.h>
FcBool FcPatternEqualSubset(const FcPattern *pa, const FcPattern *pb, const
FcObjectSet *os);
```

## Description

Returns whether  $p_a$  and  $p_b$  have exactly the same values for all of the objects in  $os$ .

## Version

Fontconfig version 2.3.97

# FcPatternHash

## Name

`FcPatternHash` — Compute a pattern hash value

## Synopsis

```
#include <fontconfig.h>
FcChar32 FcPatternHash(const FcPattern *p);
```

## Description

Returns a 32-bit number which is the same for any two patterns which are equal.

## Version

Fontconfig version 2.3.97

# FcPatternAdd

## Name

FcPatternAdd — Add a value to a pattern

## Synopsis

```
#include <fontconfig.h>
FcBool FcPatternAdd(FcPattern *p, const char *object, FcValuevalue,
FcBoolappend);
```

## Description

Adds a single value to the list of values associated with the property named ‘object’. If ‘append’ is FcTrue, the value is added at the end of any existing list, otherwise it is inserted at the begining. ‘value’ is saved (with FcValueSave) when inserted into the pattern so that the library retains no reference to any application-supplied data structure.

## Version

Fontconfig version 2.3.97

# FcPatternAddWeak

## Name

FcPatternAddWeak — Add a value to a pattern with weak binding

## Synopsis

```
#include <fontconfig.h>
FcBool FcPatternAddWeak(FcPattern *p, const char *object, FcValuevalue,
FcBoolappend);
```

## Description

`FcPatternAddWeak` is essentially the same as `FcPatternAdd` except that any values added to the list have binding *weak* instead of *strong*.

## Version

Fontconfig version 2.3.97

# FcPatternAdd-Type

## Name

`FcPatternAddInteger`, `FcPatternAddDouble`, `FcPatternAddString`,  
`FcPatternAddMatrix`, `FcPatternAddCharSet`, `FcPatternAddBool` — Add a typed  
 value to a pattern

## Synopsis

```
#include <fontconfig.h>
FcBool FcPatternAddInteger(FcPattern *p, const char *object, inti);
FcBool FcPatternAddDouble(FcPattern *p, const char *object, doubled);
FcBool FcPatternAddString(FcPattern *p, const char *object, const char *s);
FcBool FcPatternAddMatrix(FcPattern *p, const char *object, const FcMatrix
*m);
FcBool FcPatternAddCharSet(FcPattern *p, const char *object, const Fc CharSet
*c);
FcBool FcPatternAddBool(FcPattern *p, const char *object, FcBoolb);
```

## Description

These are all convenience functions that insert objects of the specified type into the pattern. Use these in preference to `FcPatternAdd` as they will provide compile-time typechecking. These all append values to any existing list of values.

## Version

Fontconfig version 2.3.97

# FcPatternGet

## Name

**FcPatternGet** — Return a value from a pattern

## Synopsis

```
#include <fontconfig.h>
FcResult FcPatternGet(FcPattern *p, const char *object, int id, FcValue *v);
```

## Description

Returns in *v* the *id*'th value associated with the property *object*. The value returned is not a copy, but rather refers to the data stored within the pattern directly. Applications must not free this value.

## Version

Fontconfig version 2.3.97

# FcPatternGet-Type

## Name

**FcPatternGetInteger**, **FcPatternGetDouble**, **FcPatternGetString**,  
**FcPatternGetMatrix**, **FcPatternGetCharSet**, **FcPatternGetBool** — Return a typed  
value from a pattern

## Synopsis

```
#include <fontconfig.h>
FcResult FcPatternGetInteger(FcPattern *p, const char *object, intn, int *i);
FcResult FcPatternGetDouble(FcPattern *p, const char *object, intn, double
*d);
FcResult FcPatternGetString(FcPattern *p, const char *object, intn, char
**consts);
FcResult FcPatternGetMatrix(FcPattern *p, const char *object, intn, FcMatrix
**s);
FcResult FcPatternGetCharSet(FcPattern *p, const char *object, intn,
Fc CharSet **c);
FcResult FcPatternGetBool(FcPattern *p, const char *object, intn, FcBool *b);
```

## Description

These are convenience functions that call FcPatternGet and verify that the returned data is of the expected type. They return FcResultTypeMismatch if this is not the case. Note that these (like FcPatternGet) do not make a copy of any data structure referenced by the return value. Use these in preference to FcPatternGet to provide compile-time typechecking.

## Version

Fontconfig version 2.3.97

# FcPatternBuild

## Name

`FcPatternBuild`, `FcPatternVaBuild` — Create patterns from arguments

## Synopsis

```
#include <fontconfig.h>
FcPattern * FcPatternBuild(FcPattern *orig, ...);
FcPattern * FcPatternVaBuild(FcPattern *orig, va_listva);
```

## Description

Builds a pattern using a list of objects, types and values. Each value to be entered in the pattern is specified with three arguments:

1. Object name, a string describing the property to be added.
2. Object type, one of the FcType enumerated values
3. Value, not an FcValue, but the raw type as passed to any of the FcPatternAdd<type> functions.  
Must match the type of the second argument.

The argument list is terminated by a null object name, no object type nor value need be passed for this. The values are added to ‘pattern’, if ‘pattern’ is null, a new pattern is created. In either case, the pattern is returned. Example

```
pattern = FcPatternBuild (0, FC_FAMILY, FcTypeString, "Times", (char *) 0);
```

FcPatternVaBuild is used when the arguments are already in the form of a varargs value.

## Version

Fontconfig version 2.3.97

# FcPatternDel

## Name

`FcPatternDel` — Delete a property from a pattern

## Synopsis

```
#include <fontconfig.h>
FcBool FcPatternDel(FcPattern *p, const char *object);
```

## Description

Deletes all values associated with the property ‘object’, returning whether the property existed or not.

## **Version**

Fontconfig version 2.3.97

# **FcPatternRemove**

## **Name**

`FcPatternRemove` — Remove one object of the specified type from the pattern

## **Synopsis**

```
#include <fontconfig.h>
FcBool FcPatternRemove(FcPattern *p, const char *object, int id);
```

## **Description**

Removes the value associated with the property ‘object’ at position ‘id’, returning whether the property existed and had a value at that position or not.

## **Version**

Fontconfig version 2.3.97

# **FcPatternPrint**

## **Name**

`FcPatternPrint` — Print a pattern for debugging

## Synopsis

```
#include <fontconfig.h>
void FcPatternPrint(const FcPattern *p);
```

## Description

Prints an easily readable version of the pattern to stdout. There is no provision for reparsing data in this format, it's just for diagnostics and debugging.

## Version

Fontconfig version 2.3.97

# **FcDefaultSubstitute**

## Name

`FcDefaultSubstitute` — Perform default substitutions in a pattern

## Synopsis

```
#include <fontconfig.h>
void FcDefaultSubstitute(FcPattern *pattern);
```

## Description

Supplies default values for underspecified font patterns:

- Patterns without a specified style or weight are set to Medium
- Patterns without a specified style or slant are set to Roman
- Patterns without a specified pixel size are given one computed from any specified point size (default 12), dpi (default 75) and scale (default 1).

## **Version**

Fontconfig version 2.3.97

# **FcNameParse**

## **Name**

`FcNameParse` — Parse a pattern string

## **Synopsis**

```
#include <fontconfig.h>
FcPattern * FcNameParse(const char *name);
```

## **Description**

Converts *name* from the standard text format described above into a pattern.

## **Version**

Fontconfig version 2.3.97

# **FcNameUnparse**

## **Name**

`FcNameUnparse` — Convert a pattern back into a string that can be parsed

## Synopsis

```
#include <fontconfig.h>
FcChar8 * FcNameUnparse(FcPattern *pat);
```

## Description

Converts the given pattern into the standard text format described above. The return value is not static, but instead refers to newly allocated memory which should be freed by the caller.

## Version

Fontconfig version 2.3.97

## 4.3. FcFontSet

An FcFontSet simply holds a list of patterns; these are used to return the results of listing available fonts.

## FcFontSetCreate

### Name

`FcFontSetCreate` — Create a font set

## Synopsis

```
#include <fontconfig.h>
FcFontSet * FcFontSetCreate(void);
```

## Description

Creates an empty font set.

## Version

Fontconfig version 2.3.97

# FcFontSetDestroy

## Name

`FcFontSetDestroy` — Destroy a font set

## Synopsis

```
#include <fontconfig.h>
void FcFontSetDestroy(FcFontSet *s);
```

## Description

Destroys a font set. Note that this destroys any referenced patterns as well.

## Version

Fontconfig version 2.3.97

# FcFontSetAdd

## Name

`FcFontSetAdd` — Add to a font set

## Synopsis

```
#include <fontconfig.h>
```

```
FcBool FcFontSetAdd(FcFontSet *s, FcPattern *font);
```

## Description

Adds a pattern to a font set. Note that the pattern is not copied before being inserted into the set.

## Version

Fontconfig version 2.3.97

## 4.4. FcObjectSet

An FcObjectSet holds a list of pattern property names; it is used to indicate which properties are to be returned in the patterns from FcFontList.

## FcObjectSetCreate

### Name

`FcObjectSetCreate` — Create an object set

### Synopsis

```
#include <fontconfig.h>
FcObjectSet * FcObjectSetCreate(void);
```

## Description

Creates an empty set.

## Version

Fontconfig version 2.3.97

# FcObjectSetAdd

## Name

`FcObjectSetAdd` — Add to an object set

## Synopsis

```
#include <fontconfig.h>
FcBool FcObjectSetAdd(FcObjectSet *os, const char *object);
```

## Description

Adds a property name to the set.

## Version

Fontconfig version 2.3.97

# FcObjectSetDestroy

## Name

`FcObjectSetDestroy` — Destroy an object set

## Synopsis

```
#include <fontconfig.h>
void FcObjectSetDestroy(FcObjectSet *os);
```

## Description

Destroys an object set.

## Version

Fontconfig version 2.3.97

# FcObjectSetBuild

## Name

`FcObjectSetBuild`, `FcObjectSetVaBuild` — Build object set from args

## Synopsis

```
#include <fontconfig.h>
FcObjectSet * FcObjectSetBuild(const char *first, ...);
FcObjectSet * FcObjectSetVaBuild(const char *first, va_listva);
```

## Description

These build an object set from a null-terminated list of property names.

## Version

Fontconfig version 2.3.97

## 4.5. FreeType specific functions

While the fontconfig library doesn't insist that FreeType be used as the rasterization mechanism for fonts, it does provide some convenience functions.

### FcFreeTypeCharIndex

#### Name

FcFreeTypeCharIndex — map Unicode to glyph id

#### Synopsis

```
#include <fontconfig.h>
#include <fcfreetype.h>
FT_UInt FcFreeTypeCharIndex(FT_Faceface, FcChar32ucs4);
```

#### Description

Maps a Unicode char to a glyph index. This function uses information from several possible underlying encoding tables to work around broken fonts. As a result, this function isn't designed to be used in performance sensitive areas; results from this function are intended to be cached by higher level functions.

#### Version

Fontconfig version 2.3.97

## FcFreeTypeCharSet

### Name

FcFreeTypeCharSet — compute unicode coverage

### Synopsis

```
#include <fontconfig.h>
#include <fcfreetype.h>
Fc CharSet * FcFreeTypeCharSet(FT_Face face, FcBlanks *blanks);
```

### Description

Scans a FreeType face and returns the set of encoded Unicode chars. This scans several encoding tables to build as complete a list as possible. If 'blanks' is not 0, the glyphs in the font are examined and any blank glyphs not in 'blanks' are not placed in the returned Fc CharSet.

### Version

Fontconfig version 2.3.97

## FcFreeTypeQuery

### Name

FcFreeTypeQuery — compute font file pattern

### Synopsis

```
#include <fontconfig.h>
#include <fcfreetype.h>
Fc Pattern * FcFreeTypeQuery(const char *file, int id, FcBlanks *blanks, int
*count);
```

## Description

Constructs a pattern representing the 'id'th font in 'file'. The number of fonts in 'file' is returned in 'count'.

## Version

Fontconfig version 2.3.97

## 4.6. FcValue

FcValue is a structure containing a type tag and a union of all possible datatypes. The tag is an enum of type *FcType* and is intended to provide a measure of run-time typechecking, although that depends on careful programming.

## FcValueDestroy

### Name

`FcValueDestroy` — Free a value

### Synopsis

```
#include <fontconfig.h>
void FcValueDestroy(FcValuev);
```

## Description

Frees any memory referenced by *v*. Values of type *FcTypeString*, *FcTypeMatrix* and *FcTypeCharSet* reference memory, the other types do not.

## Version

Fontconfig version 2.3.97

## FcValueSave

### Name

FcValueSave — Copy a value

### Synopsis

```
#include <fontconfig.h>
FcValue FcValueSave(FcValue* v);
```

### Description

Returns a copy of *v* duplicating any object referenced by it so that *v* may be safely destroyed without harming the new value.

### Version

Fontconfig version 2.3.97

## 4.7. FcCharSet

An Fc CharSet is a boolean array indicating a set of unicode chars. Those associated with a font are marked constant and cannot be edited. Fc CharSetS may be reference counted internally to reduce memory consumption; this may be visible to applications as the result of Fc CharSetCopy may return its argument, and that CharSet may remain unmodifiable.

## Fc CharSetCreate

### Name

Fc CharSetCreate — Create an empty character set

## Synopsis

```
#include <fontconfig.h>
FcCharSet * Fc CharSetCreate(void);
```

## Description

`Fc CharSetCreate` allocates and initializes a new empty character set object.

## Version

Fontconfig version 2.3.97

# **Fc CharSetDestroy**

## Name

`Fc CharSetDestroy` — Destroy a character set

## Synopsis

```
#include <fontconfig.h>
void Fc CharSetDestroy(Fc CharSet *fcs);
```

## Description

`Fc CharSetDestroy` decrements the reference count *fcs*. If the reference count becomes zero, all memory referenced is freed.

## Version

Fontconfig version 2.3.97

## Fc CharSetAddChar

### Name

Fc CharSetAddChar — Add a character to a charset

### Synopsis

```
#include <fontconfig.h>
FcBool Fc CharSetAddChar(Fc CharSet *fcs, Fc Char32 ucs4);
```

### Description

Fc CharSetAddChar adds a single unicode char to the set, returning FcFalse on failure, either as a result of a constant set or from running out of memory.

### Version

Fontconfig version 2.3.97

## Fc CharSetCopy

### Name

Fc CharSetCopy — Copy a charset

### Synopsis

```
#include <fontconfig.h>
Fc CharSet * Fc CharSetCopy(Fc CharSet *src);
```

## Description

Makes a copy of *src*; note that this may not actually do anything more than increment the reference count on *src*.

## Version

Fontconfig version 2.3.97

# FcCharSetEqual

## Name

`FcCharSetEqual` — Compare two charsets

## Synopsis

```
#include <fontconfig.h>
FcBool FcCharSetEqual(const Fc CharSet *a, const Fc CharSet *b);
```

## Description

Returns whether *a* and *b* contain the same set of unicode chars.

## Version

Fontconfig version 2.3.97

## Fc CharSetIntersect

### Name

Fc CharSetIntersect — Intersect charsets

### Synopsis

```
#include <fontconfig.h>
Fc CharSet * Fc CharSetIntersect(const Fc CharSet *a, const Fc CharSet *b);
```

### Description

Returns a set including only those chars found in both *a* and *b*.

### Version

Fontconfig version 2.3.97

## Fc CharSetUnion

### Name

Fc CharSetUnion — Add charsets

### Synopsis

```
#include <fontconfig.h>
Fc CharSet * Fc CharSetUnion(const Fc CharSet *a, const Fc CharSet *b);
```

## Description

Returns a set including only those chars found in either *a* or *b*.

## Version

Fontconfig version 2.3.97

# Fc CharSetSubtract

## Name

`Fc CharSetSubtract` — Subtract charsets

## Synopsis

```
#include <fontconfig.h>
Fc CharSet * Fc CharSetSubtract(const Fc CharSet *a, const Fc CharSet *b);
```

## Description

Returns a set including only those chars found in *a* but not *b*.

## Version

Fontconfig version 2.3.97

## Fc CharSetHasChar

### Name

Fc CharSetHasChar — Check a charset for a char

### Synopsis

```
#include <fontconfig.h>
FcBool Fc CharSetHasChar(const Fc CharSet *fcs, Fc Char32 ucs4);
```

### Description

Returns whether *fcs* contains the char *ucs4*.

### Version

Fontconfig version 2.3.97

## Fc CharSetCount

### Name

Fc CharSetCount — Count entries in a charset

### Synopsis

```
#include <fontconfig.h>
Fc Char32 Fc CharSetCount(const Fc CharSet *a);
```

## Description

Returns the total number of unicode chars in *a*.

## Version

Fontconfig version 2.3.97

# Fc CharSetIntersectCount

## Name

`Fc CharSetIntersectCount` — Intersect and count charsets

## Synopsis

```
#include <fontconfig.h>
FcChar32 Fc CharSetIntersectCount(const Fc CharSet *a, const Fc CharSet *b);
```

## Description

Returns the number of chars that are in both *a* and *b*.

## Version

Fontconfig version 2.3.97

## Fc CharSetSubtractCount

### Name

Fc CharSetSubtractCount — Subtract and count charsets

### Synopsis

```
#include <fontconfig.h>
FcChar32 Fc CharSetSubtractCount(const Fc CharSet *a, const Fc CharSet *b);
```

### Description

Returns the number of chars that are in *a* but not in *b*.

### Version

Fontconfig version 2.3.97

## Fc CharSetIsSubset

### Name

Fc CharSetIsSubset — Test for charset inclusion

### Synopsis

```
#include <fontconfig.h>
FcBool Fc CharSetIsSubset(const Fc CharSet *a, const Fc CharSet *b);
```

## Description

Returns whether  $a$  is a subset of  $b$ .

## Version

Fontconfig version 2.3.97

# Fc CharSetFirstPage

## Name

`Fc CharSetFirstPage` — Start enumerating charset contents

## Synopsis

```
#include <fontconfig.h>
FcChar32 Fc CharSetFirstPage(const Fc CharSet *a,
FcChar32[FC_CHARSET_MAP_SIZE]map, FcChar32 *next);
```

## Description

Builds an array of bits marking the first page of Unicode coverage of  $a$ . Returns the base of the array.  $next$  contains the next page in the font.

## Version

Fontconfig version 2.3.97

## FcCharSetNextPage

### Name

FcCharSetNextPage — Continue enumerating charset contents

### Synopsis

```
#include <fontconfig.h>
FcChar32 FcCharSetNextPage(const FcCharSet *a,
FcChar32[FC_CHARSET_MAP_SIZE]map, FcChar32 *next);
```

### Description

Builds an array of bits marking the Unicode coverage of *a* for page *\*next*. Returns the base of the array. *next* contains the next page in the font.

### Version

Fontconfig version 2.3.97

## 4.8. FcMatrix

FcMatrix structures hold an affine transformation in matrix form.

## FcMatrixInit

### Name

FcMatrixInit — initialize an FcMatrix structure

## Synopsis

```
#include <fontconfig.h>
void FcMatrixInit(FcMatrix *matrix);
```

## Description

`FcMatrixInit` initializes *matrix* to the identity matrix.

## Version

Fontconfig version 2.3.97

# **FcMatrixCopy**

## Name

`FcMatrixCopy` — Copy a matrix

## Synopsis

```
#include <fontconfig.h>
void FcMatrixCopy(const FcMatrix *matrix);
```

## Description

`FcMatrixCopy` allocates a new `FcMatrix` and copies *mat* into it.

## Version

Fontconfig version 2.3.97

## FcMatrixEqual

### Name

FcMatrixEqual — Compare two matrices

### Synopsis

```
#include <fontconfig.h>
void FcMatrixEqual(const FcMatrix *matrix1, const FcMatrix *matrix2);
```

### Description

FcMatrixEqual compares *matrix1* and *matrix2* returning FcTrue when they are equal and FcFalse when they are not.

### Version

Fontconfig version 2.3.97

## FcMatrixMultiply

### Name

FcMatrixMultiply — Multiply matrices

### Synopsis

```
#include <fontconfig.h>
void FcMatrixMultiply(FcMatrix *result, const FcMatrix *matrix1, const
FcMatrix *matrix2);
```

## Description

`FcMatrixMultiply` multiplies `matrix1` and `matrix2` storing the result in `result`.

## Version

Fontconfig version 2.3.97

# FcMatrixRotate

## Name

`FcMatrixRotate` — Rotate a matrix

## Synopsis

```
#include <fontconfig.h>
void FcMatrixRotate(FcMatrix *matrix, doublecos, doublesin);
```

## Description

`FcMatrixRotate` rotates `matrix` by the angle who's sine is `sin` and cosine is `cos`. This is done by multiplying by the matrix:

$$\begin{array}{cc} \cos & -\sin \\ \sin & \cos \end{array}$$

## Version

Fontconfig version 2.3.97

## FcMatrixScale

### Name

FcMatrixScale — Scale a matrix

### Synopsis

```
#include <fontconfig.h>
void FcMatrixScale(FcMatrix *matrix, doublesx, doubledy);
```

### Description

FcMatrixScale multiplies *matrix* x values by *sx* and y values by *sy*. This is done by multiplying by the matrix:

sx	0
0	sy

### Version

Fontconfig version 2.3.97

## FcMatrixShear

### Name

FcMatrixShear — Shear a matrix

### Synopsis

```
#include <fontconfig.h>
void FcMatrixShear(FcMatrix *matrix, doublesh, doublesv);
```

## Description

`FcMatrixShare` shears *matrix* horizontally by *sh* and vertically by *sv*. This is done by multiplying by the matrix:

```
1   sh
sv  1
```

## Version

Fontconfig version 2.3.97

## 4.9. FcConfig

An FcConfig object holds the internal representation of a configuration. There is a default configuration which applications may use by passing 0 to any function using the data within an FcConfig.

### FcConfigCreate

#### Name

`FcConfigCreate` — Create a configuration

#### Synopsis

```
#include <fontconfig.h>
FcConfig * FcConfigCreate(void);
```

#### Description

Creates an empty configuration.

## **Version**

Fontconfig version 2.3.97

# **FcConfigDestroy**

## **Name**

`FcConfigDestroy` — Destroy a configuration

## **Synopsis**

```
#include <fontconfig.h>
void FcConfigDestroy(FcConfig *config);
```

## **Description**

Destroys a configuration and any data associated with it. Note that calling this function with the return from `FcConfigGetCurrent` will place the library in an indeterminate state.

## **Version**

Fontconfig version 2.3.97

# **FcConfigSetCurrent**

## **Name**

`FcConfigSetCurrent` — Set configuration as default

## Synopsis

```
#include <fontconfig.h>
FcBool FcConfigSetCurrent(FcConfig *config);
```

## Description

Sets the current default configuration to *config*. Implicitly calls FcConfigBuildFonts if necessary, returning FcFalse if that call fails.

## Version

Fontconfig version 2.3.97

# **FcConfigGetCurrent**

## Name

`FcConfigGetCurrent` — Return current configuration

## Synopsis

```
#include <fontconfig.h>
FcConfig * FcConfigGetCurrent(void);
```

## Description

Returns the current default configuration.

## Version

Fontconfig version 2.3.97

## FcConfigUptoDate

### Name

FcConfigUptoDate — Check timestamps on config files

### Synopsis

```
#include <fontconfig.h>
FcBool FcConfigUptoDate(FcConfig *config);
```

### Description

Checks all of the files related to *config* and returns whether the in-memory version is in sync with the disk version.

### Version

Fontconfig version 2.3.97

## FcConfigBuildFonts

### Name

FcConfigBuildFonts — Build font database

### Synopsis

```
#include <fontconfig.h>
FcBool FcConfigBuildFonts(FcConfig *config);
```

## Description

Builds the set of available fonts for the given configuration. Note that any changes to the configuration after this call have indeterminate effects. Returns FcFalse if this operation runs out of memory.

## Version

Fontconfig version 2.3.97

# FcConfigGetConfigDirs

## Name

FcConfigGetConfigDirs — Get config directories

## Synopsis

```
#include <fontconfig.h>
FcStrList * FcConfigGetConfigDirs(FcConfig *config);
```

## Description

Returns the list of font directories specified in the configuration files for *config*. Does not include any subdirectories.

## Version

Fontconfig version 2.3.97

## FcConfigGetFontDirs

### Name

FcConfigGetFontDirs — Get font directories

### Synopsis

```
#include <fontconfig.h>
FcStrList * FcConfigGetFontDirs(FcConfig *config);
```

### Description

Returns the list of font directories in *config*. This includes the configured font directories along with any directories below those in the filesystem.

### Version

Fontconfig version 2.3.97

## FcConfigGetConfigFiles

### Name

FcConfigGetConfigFiles — Get config files

### Synopsis

```
#include <fontconfig.h>
FcStrList * FcConfigGetConfigFiles(FcConfig *config);
```

## Description

Returns the list of known configuration files used to generate *config*. Note that this will not include any configuration done with FcConfigParse.

## Version

Fontconfig version 2.3.97

# FcConfigGetCache

## Name

FcConfigGetCache — Get cache filename

## Synopsis

```
#include <fontconfig.h>
char * FcConfigGetCache(FcConfig *config);
```

## Description

Returns the name of the file used to store per-user font information.

## Version

Fontconfig version 2.3.97

## FcConfigGetFonts

### Name

FcConfigGetFonts — Get config font set

### Synopsis

```
#include <fontconfig.h>
FcFontSet * FcConfigGetFonts (FcConfig *config, FcSetNameSet);
```

### Description

Returns one of the two sets of fonts from the configuration as specified by *set*.

### Version

Fontconfig version 2.3.97

## FcConfigGetBlanks

### Name

FcConfigGetBlanks — Get config blanks

### Synopsis

```
#include <fontconfig.h>
FcBlanks * FcConfigGetBlanks (FcConfig *config);
```

## Description

Returns the FcBlanks object associated with the given configuration, if no blanks were present in the configuration, this function will return 0.

## Version

Fontconfig version 2.3.97

# FcConfigGetRescanInterval

## Name

`FcConfigGetRescanInterval` — Get config rescan interval

## Synopsis

```
#include <fontconfig.h>
int FcConfigGetRescanInterval (FcConfig *config);
```

## Description

Returns the interval between automatic checks of the configuration (in seconds) specified in *config*. The configuration is checked during a call to `FcFontList` when this interval has passed since the last check.

## Version

Fontconfig version 2.3.97

## **FcConfigSetRescanInveral**

### **Name**

FcConfigSetRescanInveral — Set config rescan interval

### **Synopsis**

```
#include <fontconfig.h>
FcBool FcConfigSetRescanInveral(FcConfig *config, int rescanInterval);
```

### **Description**

Sets the rescan interval; returns FcFalse if an error occurred.

### **Version**

Fontconfig version 2.3.97

## **FcConfigAppFontAddFile**

### **Name**

FcConfigAppFontAddFile — Add font file to font database

### **Synopsis**

```
#include <fontconfig.h>
FcBool FcConfigAppFontAddFile(FcConfig *config, const char *file);
```

## Description

Adds an application-specific font to the configuration.

## Version

Fontconfig version 2.3.97

# FcConfigAppFontAddDir

## Name

`FcConfigAppFontAddDir` — Add fonts from directory to font database

## Synopsis

```
#include <fontconfig.h>
FcBool FcConfigAppFontAddDir(FcConfig *config, const char *);
```

## Description

Scans the specified directory for fonts, adding each one found to the application-specific set of fonts.

## Version

Fontconfig version 2.3.97

## FcConfigAppFontClear

### Name

FcConfigAppFontClear — Remove all app fonts from font database

### Synopsis

```
#include <fontconfig.h>
void FcConfigAppFontClear(FcConfig *config);
```

### Description

Clears the set of application-specific fonts.

### Version

Fontconfig version 2.3.97

## FcConfigSubstituteWithPat

### Name

FcConfigSubstituteWithPat — Execute substitutions

### Synopsis

```
#include <fontconfig.h>
FcBool FcConfigSubstituteWithPat(FcConfig *config, FcPattern *p, FcPattern
*p_pat, FcMatchKindkind);
```

## Description

Performs the sequence of pattern modification operations, if *kind* is FcMatchPattern, then those tagged as pattern operations are applied, else if *kind* is FcMatchFont, those tagged as font operations are applied and p\_pat is used for <test> elements with target=pattern.

## Version

Fontconfig version 2.3.97

# FcConfigSubstitute

## Name

`FcConfigSubstitute` — Execute substitutions

## Synopsis

```
#include <fontconfig.h>
FcBool FcConfigSubstitute(FcConfig *config, FcPattern *p, FcMatchKind kind);
```

## Description

Calls `FcConfigSubstituteWithPat` setting p\_pat to NULL.

## Version

Fontconfig version 2.3.97

# FcFontMatch

## Name

FcFontMatch — Return best font

## Synopsis

```
#include <fontconfig.h>
FcPattern * FcFontMatch(FcConfig *config, FcPattern *p, FcResult *result);
```

## Description

Returns the font in *config* most close matching *p*. This function should be called only after FcConfigSubstitute and FcDefaultSubstitute have been called for *p*; otherwise the results will not be correct.

## Version

Fontconfig version 2.3.97

# FcFontSort

## Name

FcFontSort — Return list of matching fonts

## Synopsis

```
#include <fontconfig.h>
FcFontSet * FcFontSort(FcConfig *config, FcPattern *p, FcBool trim, Fc CharSet
**csp, FcResult *result);
```

## Description

Returns the list of fonts sorted by closeness to *p*. If *trim* is FcTrue, elements in the list which don't include Unicode coverage not provided by earlier elements in the list are elided. The union of Unicode coverage of all of the fonts is returned in *csp*, if *csp* is not NULL. This function should be called only after FcConfigSubstitute and FcDefaultSubstitute have been called for *p*; otherwise the results will not be correct.

The returned FcFontSet references FcPattern structures which may be shared by the return value from multiple FcFontSort calls, applications must not modify these patterns. Instead, they should be passed, along with *p* to FcFontRenderPrepare which combines them into a complete pattern.

The FcFontSet returned by FcFontSort is destroyed by calling FcFontSetDestroy.

## Version

Fontconfig version 2.3.97

# FcFontRenderPrepare

## Name

`FcFontRenderPrepare` — Prepare pattern for loading font file

## Synopsis

```
#include <fontconfig.h>
FcPattern * FcFontRenderPrepare(FcConfig *config, FcPattern *pat, FcPattern
*font);
```

## Description

Creates a new pattern consisting of elements of *font* not appearing in *pat*, elements of *pat* not appearing in *font* and the best matching value from *pat* for elements appearing in both. The result is passed to FcConfigSubstitute with *kind* FcMatchFont and then returned.

## **Version**

Fontconfig version 2.3.97

# **FcFontList**

## **Name**

`FcFontList` — List fonts

## **Synopsis**

```
#include <fontconfig.h>
FcFontSet * FcFontList(FcConfig *config, FcPattern *p, FcObjectSet *os);
```

## **Description**

Selects fonts matching *p*, creates patterns from those fonts containing only the objects in *os* and returns the set of unique such patterns.

## **Version**

Fontconfig version 2.3.97

# **FcConfigFilename**

## **Name**

`FcConfigFilename` — Find a config file

## Synopsis

```
#include <fontconfig.h>
char * FcConfigFilename(const char *name);
```

## Description

Given the specified external entity name, return the associated filename. This provides applications a way to convert various configuration file references into filename form.

A null or empty *name* indicates that the default configuration file should be used; which file this references can be overridden with the FC\_CONFIG\_FILE environment variable. Next, if the name starts with ~, it refers to a file in the current users home directory. Otherwise if the name doesn't start with '/', it refers to a file in the default configuration directory; the built-in default directory can be overridden with the FC\_CONFIG\_DIR environment variable.

## Version

Fontconfig version 2.3.97

# FcConfigParseAndLoad

## Name

`FcConfigParseAndLoad` — load a configuration file

## Synopsis

```
#include <fontconfig.h>
FcBool FcConfigParseAndLoad(FcConfig *config, const FcChar8 *file);
```

## Description

Walks the configuration in 'file' and constructs the internal representation in 'config'. Any include files referenced from within 'file' will be loaded with FcConfigLoad and also parsed. If 'complain' is FcFalse, no warning will be displayed if 'file' does not exist.

## Version

Fontconfig version 2.3.97

# FcConfigNormalizeFontDir

## Name

FcConfigNormalizeFontDir — normalize a font directory

## Synopsis

```
#include <fontconfig.h>
const FcChar8 * FcConfigNormalizeFontDir(FcConfig *config, const FcChar8
*dir);
```

## Description

Converts the directory name given in 'dir' to a normal form, i.e. one of the forms which are derived from the font directories specified in the config file.

## Version

Fontconfig version 2.3.97

## 4.10. FcObjectType

Provides for application-specified font name object types so that new pattern elements can be generated from font names.

# FcNameRegisterObjectTypes

## Name

`FcNameRegisterObjectTypes` — Register object types

## Synopsis

```
#include <fontconfig.h>
FcBool FcNameRegisterObjectTypes(const FcObjectType *types, int ntype);
```

## Description

Register *ntype* new object types.

## Version

Fontconfig version 2.3.97

# FcNameUnregisterObjectTypes

## Name

`FcNameUnregisterObjectTypes` — Unregister object types

## Synopsis

```
#include <fontconfig.h>
FcBool FcNameUnregisterObjectTypes(const FcObjectType *types, int ntype);
```

## Description

Unregister *ntype* object types.

## Version

Fontconfig version 2.3.97

# FcNameGetObjectType

## Name

`FcNameGetObjectType` — Lookup an object type

## Synopsis

```
#include <fontconfig.h>
const FcObjectType * FcNameGetObjectType(const char *object);
```

## Description

Return the object type for the pattern element named *object*.

## Version

Fontconfig version 2.3.97

## 4.11. FcConstant

Provides for application-specified symbolic constants for font names.

# FcNameRegisterConstants

## Name

`FcNameRegisterConstants` — Register symbolic constants

## Synopsis

```
#include <fontconfig.h>
FcBool FcNameRegisterConstants(const FcConstant *consts, int nconsts);
```

## Description

Register *nconsts* new symbolic constants.

## Version

Fontconfig version 2.3.97

# FcNameUnregisterConstants

## Name

`FcNameUnregisterConstants` — Unregister symbolic constants

## Synopsis

```
#include <fontconfig.h>
FcBool FcNameUnregisterConstants(const FcConstant *consts, int nconsts);
```

## Description

Unregister *nconsts* symbolic constants.

## Version

Fontconfig version 2.3.97

# FcNameGetConstant

## Name

`FcNameGetConstant` — Lookup symbolic constant

## Synopsis

```
#include <fontconfig.h>
const FcConstant * FcNameGetConstant(FcChar8 *string);
```

## Description

Return the FcConstant structure related to symbolic constant *string*.

## Version

Fontconfig version 2.3.97

# FcNameConstant

## Name

FcNameConstant — Get the value for a symbolic constant

## Synopsis

```
#include <fontconfig.h>
FcBool FcNameConstant(FcChar8 *string, int *result);
```

## Description

Returns whether a symbolic constant with name *string* is registered, placing the value of the constant in *result* if present.

## Version

Fontconfig version 2.3.97

## 4.12. FcBlanks

An FcBlanks object holds a list of Unicode chars which are expected to be blank when drawn. When scanning new fonts, any glyphs which are empty and not in this list will be assumed to be broken and not placed in the Fc CharSet associated with the font. This provides a significantly more accurate CharSet for applications.

# FcBlanksCreate

## Name

FcBlanksCreate — Create an FcBlanks

## Synopsis

```
#include <fontconfig.h>
FcBlanks * FcBlanksCreate(void);
```

## Description

Creates an empty FcBlanks object.

## Version

Fontconfig version 2.3.97

# FcBlanksDestroy

## Name

`FcBlanksDestroy` — Destroy and FcBlanks

## Synopsis

```
#include <fontconfig.h>
void FcBlanksDestroy(FcBlanks *b);
```

## Description

Destroys an FcBlanks object, freeing any associated memory.

## Version

Fontconfig version 2.3.97

## FcBlanksAdd

### Name

FcBlanksAdd — Add a character to an FcBlanks

### Synopsis

```
#include <fontconfig.h>
FcBool FcBlanksAdd(FcBlanks *b, FcChar32 ucs4);
```

### Description

Adds a single character to an FcBlanks object, returning FcFalse if this process ran out of memory.

### Version

Fontconfig version 2.3.97

## FcBlanksIsMember

### Name

FcBlanksIsMember — Query membership in an FcBlanks

### Synopsis

```
#include <fontconfig.h>
FcBool FcBlanksIsMember(FcBlanks *b, FcChar32 ucs4);
```

## Description

Returns whether the specified FcBlanks object contains the indicated Unicode value.

## Version

Fontconfig version 2.3.97

## 4.13. FcAtomic

These functions provide a safe way to update config files, allowing ongoing reading of the old config file while locked for writing and ensuring that a consistent and complete version of the config file is always available.

## FcAtomicCreate

### Name

`FcAtomicCreate` — create an FcAtomic object

### Synopsis

```
#include <fontconfig.h>
FcAtomic * FcAtomicCreate(const FcChar8 *file);
```

## Description

Creates a data structure containing data needed to control access to *file*. Writing is done to a separate file. Once that file is complete, the original configuration file is atomically replaced so that reading process always see a consistent and complete file without the need to lock for reading.

## Version

Fontconfig version 2.3.97

## FcAtomicLock

### Name

FcAtomicLock — lock a file

### Synopsis

```
#include <fontconfig.h>
FcBool FcAtomicLock(FcAtomic *atomic);
```

### Description

Attempts to lock the file referenced by *atomic*. Returns FcFalse if the file is locked by another process, else returns FcTrue and leaves the file locked.

### Version

Fontconfig version 2.3.97

## FcAtomicNewFile

### Name

FcAtomicNewFile — return new temporary file name

### Synopsis

```
#include <fontconfig.h>
FcChar8 * FcAtomicNewFile(FcAtomic *atomic);
```

## Description

Returns the filename for writing a new version of the file referenced by *atomic*.

## Version

Fontconfig version 2.3.97

# FcAtomicOrigFile

## Name

`FcAtomicOrigFile` — return original file name

## Synopsis

```
#include <fontconfig.h>
FcChar8 * FcAtomicOrigFile(FcAtomic *atomic);
```

## Description

Returns the file referenced by *atomic*.

## Version

Fontconfig version 2.3.97

## FcAtomicReplaceOrig

### Name

FcAtomicReplaceOrig — replace original with new

### Synopsis

```
#include <fontconfig.h>
FcBool FcAtomicReplaceOrig(FcAtomic *atomic);
```

### Description

Replaces the original file referenced by *atomic* with the new file.

### Version

Fontconfig version 2.3.97

## FcAtomicDeleteNew

### Name

FcAtomicDeleteNew — delete new file

### Synopsis

```
#include <fontconfig.h>
void FcAtomicDeleteNew(FcAtomic *atomic);
```

## **Description**

Deletes the new file. Used in error recovery to back out changes.

## **Version**

Fontconfig version 2.3.97

# **FcAtomicUnlock**

## **Name**

**FcAtomicUnlock** — unlock a file

## **Synopsis**

```
#include <fontconfig.h>
void FcAtomicUnlock(FcAtomic *atomic);
```

## **Description**

Unlocks the file.

## **Version**

Fontconfig version 2.3.97

## FcAtomicDestroy

### Name

FcAtomicDestroy — destroy an FcAtomic object

### Synopsis

```
#include <fontconfig.h>
void FcAtomicDestroy(FcAtomic *atomic);
```

### Description

Destroys *atomic*.

### Version

Fontconfig version 2.3.97

## 4.14. File and Directory routines

These routines work with font files and directories, including font directory cache files.

## FcFileScan

### Name

FcFileScan — scan a font file

### Synopsis

```
#include <fontconfig.h>
FcBool FcFileScan(FcFontSet *set, FcStrSet *dirs, FcFileCache *cache,
FcBlanks *blanks, const char *file, FcBool force);
```

## Description

Scans a single file and adds all fonts found to *set*. If *force* is FcTrue, then the file is scanned even if associated information is found in *cache*. If *file* is a directory, it is added to *dirs*.

## Version

Fontconfig version 2.3.97

# FcDirScan

## Name

FcDirScan — scan a font directory

## Synopsis

```
#include <fontconfig.h>
FcBool FcDirScan(FcFontSet *set, FcStrSet *dirs, FcFileCache *cache, FcBlanks
*blanks, const char *dir, FcBool force);
```

## Description

Scans an entire directory and adds all fonts found to *set*. If *force* is FcTrue, then the directory and all files within it are scanned even if information is present in the per-directory cache file or *cache*. Any subdirectories found are added to *dirs*.

## Version

Fontconfig version 2.3.97

## FcDirSave

### Name

FcDirSave — save a directory cache

### Synopsis

```
#include <fontconfig.h>
FcBool FcDirSave(FcFontSet *set, FcStrSet *dirs, const char *dir);
```

### Description

Creates the per-directory cache file for *dir* and populates it with the fonts in *set* and subdirectories in *dirs*.

### Version

Fontconfig version 2.3.97

## FcDirCacheValid

### Name

FcDirCacheValid — check directory cache timestamp

### Synopsis

```
#include <fontconfig.h>
FcBool FcDirCacheValid(const FcChar8 *cache_file);
```

## Description

Returns FcTrue if *cache\_file* is no older than the directory containing it, else FcFalse.

## Version

Fontconfig version 2.3.97

## 4.15. FcStrSet and FcStrList

A data structure for enumerating strings, used to list directories while scanning the configuration as directories are added while scanning.

### FcStrSetCreate

#### Name

FcStrSetCreate — create a string set

#### Synopsis

```
#include <fontconfig.h>
FcStrSet * FcStrSetCreate(void);
```

#### Description

Create an empty set.

#### Version

Fontconfig version 2.3.97

## FcStrSetMember

### Name

FcStrSetMember — check set for membership

### Synopsis

```
#include <fontconfig.h>
FcBool FcStrSetMember(FcStrSet *set, const FcChar8 *s);
```

### Description

Returns whether *s* is a member of *set*.

### Version

Fontconfig version 2.3.97

## FcStrSetAdd

### Name

FcStrSetAdd — add to a string set

### Synopsis

```
#include <fontconfig.h>
FcBool FcStrSetAdd(FcStrSet *set, const FcChar8 *s);
```

## Description

Adds a copy of *s* to *set*.

## Version

Fontconfig version 2.3.97

# FcStrSetAddFilename

## Name

`FcStrSetAddFilename` — add a filename to a string set

## Synopsis

```
#include <fontconfig.h>
FcBool FcStrSetAddFilename(FcStrSet *set, const FcChar8 *s);
```

## Description

Adds a copy *s* to *set*, The copy is created with `FcStrCopyFilename` so that leading '~' values are replaced with the value of the HOME environment variable.

## Version

Fontconfig version 2.3.97

## FcStrSetDel

### Name

FcStrSetDel — delete from a string set

### Synopsis

```
#include <fontconfig.h>
FcBool FcStrSetDel(FcStrSet *set, const FcChar8 *s);
```

### Description

Removes *s* from *set*, returning FcTrue if *s* was a member else FcFalse.

### Version

Fontconfig version 2.3.97

## FcStrSetDestroy

### Name

FcStrSetDestroy — destroy a string set

### Synopsis

```
#include <fontconfig.h>
void FcStrSetDestroy(FcStrSet *set);
```

## Description

Destroys *set*.

## Version

Fontconfig version 2.3.97

# FcStrListCreate

## Name

`FcStrListCreate` — create a string iterator

## Synopsis

```
#include <fontconfig.h>
FcStrList * FcStrListCreate(FcStrSet *set);
```

## Description

Creates an iterator to list the strings in *set*.

## Version

Fontconfig version 2.3.97

## FcStrListNext

### Name

FcStrListNext — get next string in iteration

### Synopsis

```
#include <fontconfig.h>
FcChar8 * FcStrListNext(FcStrList *list);
```

### Description

Returns the next string in *set*.

### Version

Fontconfig version 2.3.97

## FcStrListDone

### Name

FcStrListDone — destroy a string iterator

### Synopsis

```
#include <fontconfig.h>
void FcStrListDone(FcStrList *list);
```

## Description

Destroys the enumerator *list*.

## Version

Fontconfig version 2.3.97

## 4.16. String utilities

Fontconfig manipulates many UTF-8 strings represented with the FcChar8 type. These functions are exposed to help applications deal with these UTF-8 strings in a locale-insensitive manner.

### FcUtf8ToUcs4

#### Name

`FcUtf8ToUcs4` — convert UTF-8 to UCS4

#### Synopsis

```
#include <fontconfig.h>
int FcUtf8ToUcs4(FcChar8 *src, FcChar32 *dst, int len);
```

#### Description

Converts the next Unicode char from *src* into *dst* and returns the number of bytes containing the char. *src* must be at least *len* bytes long.

## Version

Fontconfig version 2.3.97

## FcUcs4ToUtf8

### Name

FcUcs4ToUtf8 — convert UCS4 to UTF-8

### Synopsis

```
#include <fontconfig.h>
int FcUcs4ToUtf8(FcChar32src, FcChar8dst [FC_UTF8_MAX_LEN]);
```

### Description

Converts the Unicode char from *src* into *dst* and returns the number of bytes needed to encode the char.

### Version

Fontconfig version 2.3.97

## FcUtf8Len

### Name

FcUtf8Len — count UTF-8 encoded chars

### Synopsis

```
#include <fontconfig.h>
FcBool FcUtf8Len(FcChar8 *src, intlen, int *nchar, int *wchar);
```

## Description

Counts the number of Unicode chars in *len* bytes of *src*. Places that count in *nchar*. *wchar* contains 1, 2 or 4 depending on the number of bytes needed to hold the largest unicode char counted. The return value indicates whether *src* is a well-formed UTF8 string.

## Version

Fontconfig version 2.3.97

# FcUtf16ToUcs4

## Name

`FcUtf16ToUcs4` — convert UTF-16 to UCS4

## Synopsis

```
#include <fontconfig.h>
int FcUtf16ToUcs4(FcChar8 *src, FcEndian endian, FcChar32 *dst, int len);
```

## Description

Converts the next Unicode char from *src* into *dst* and returns the number of bytes containing the char. *src* must be at least *len* bytes long. Bytes of *src* are combined into 16-bit units according to *endian*.

## Version

Fontconfig version 2.3.97

## FcUtf16Len

### Name

FcUtf16Len — count UTF-16 encoded chars

### Synopsis

```
#include <fontconfig.h>
FcBool FcUtf16Len(FcChar8 *src, FcEndian endian, int len, int *nchar, int
*wchar);
```

### Description

Counts the number of Unicode chars in *len* bytes of *src*. Bytes of *src* are combined into 16-bit units according to *endian*. Places that count in *nchar*. *wchar* contains 1, 2 or 4 depending on the number of bytes needed to hold the largest unicode char counted. The return value indicates whether *string* is a well-formed UTF16 string.

### Version

Fontconfig version 2.3.97

## FcStrCopy

### Name

FcStrCopy — duplicate a string

### Synopsis

```
#include <fontconfig.h>
FcChar8 * FcStrCopy(const FcChar8 *s);
```

## Description

Allocates memory, copies *s* and returns the resulting buffer. Yes, this is `strdup`, but that function isn't available on every platform.

## Version

Fontconfig version 2.3.97

# FcStrDowncase

## Name

`FcStrDowncase` — create a lower case translation of a string

## Synopsis

```
#include <fontconfig.h>
FcChar8 * FcStrDowncase(const FcChar8 *s);
```

## Description

Allocates memory, copies *s*, converting upper case letters to lower case and returns the allocated buffer.

## Version

Fontconfig version 2.3.97

## FcStrCopyFilename

### Name

`FcStrCopyFilename` — copy a string, expanding ‘~’

### Synopsis

```
#include <fontconfig.h>
FcChar8 * FcStrCopyFilename(const FcChar8 *s);
```

### Description

Just like `FcStrCopy` except that it converts any leading ‘~’ characters in *s* to the value of the `HOME` environment variable. Returns `NULL` if ‘~’ is present in *s* and `HOME` is unset.

### Version

Fontconfig version 2.3.97

## FcStrCmpIgnoreCase

### Name

`FcStrCmpIgnoreCase` — compare UTF-8 strings ignoring ASCII case

### Synopsis

```
#include <fontconfig.h>
int FcStrCmpIgnoreCase(const FcChar8 *s1, const FcChar8 *s2);
```

## Description

Returns the usual  $<0, 0, >0$  result of comparing  $s_1$  and  $s_2$ . This test is case-insensitive in the ASCII range and will operate properly with UTF8 encoded strings, although it does not check for well formed strings.

## Version

Fontconfig version 2.3.97

# FcStrStr

## Name

`FcStrStr` — locate UTF-8 substring

## Synopsis

```
#include <fontconfig.h>
FcChar8 * FcStrStr(const char *s1, const char *s2);
```

## Description

Returns the location of  $s_2$  in  $s_1$ . Returns NULL if  $s_2$  is not present in  $s_1$ . This test will operate properly with UTF8 encoded strings, although it does not check for well formed strings.

## Version

Fontconfig version 2.3.97

## FcStrStrIgnoreCase

### Name

FcStrStrIgnoreCase — locate UTF-8 substring ignoring ASCII case

### Synopsis

```
#include <fontconfig.h>
FcChar8 * FcStrStrIgnoreCase(const char *s1, const char *s2);
```

### Description

Returns the location of *s2* in *s1*, ignoring ASCII case. Returns NULL if *s2* is not present in *s1*. This test is case-insensitive in the ASCII range and will operate properly with UTF8 encoded strings, although it does not check for well formed strings.

### Version

Fontconfig version 2.3.97

## FcStrDirname

### Name

FcStrDirname — directory part of filename

### Synopsis

```
#include <fontconfig.h>
FcChar8 * FcStrDirname(const FcChar8 *file);
```

## Description

Returns the directory containing *file*. This is returned in newly allocated storage which should be freed when no longer needed.

## Version

Fontconfig version 2.3.97

# FcStrBasename

## Name

`FcStrBasename` — last component of filename

## Synopsis

```
#include <fontconfig.h>
FcChar8 * FcStrBasename(const FcChar8 *file);
```

## Description

Returns the filename of *file* stripped of any leading directory names. This is returned in newly allocated storage which should be freed when no longer needed.

## Version

Fontconfig version 2.3.97